



IC200SCE-SO

Scoop Ice Cream Freezer

Product Features

- Sneeze guard in curved glass
- Angled sliding lids with lock
- Storage under baskets
- Castors with brake
- Powder coated white steel inner liner
- Optional Scooping baskets for plastic tubs



Scooping basket option



Scoop wash option

Scoop ice cream freezer - angled and with serveover

The IC-SO range is our price friendly basis chest freezer with a serve over glass top. It is a quality scoop ice cream freezer for a fair price. It is perfect if you wish to add scooping ice cream sales to your business and are on a budget.

This model is the angled version with angled sliding glass lids instead of flat. The lower front of the freezer provides a better display of the content and makes it even more ideal for display of scoop ice cream.

The model is still compact and comes in varies sizes, so that it is perfect for both smaller shops and delis with limited space as well as lager shops, gas stations and supermarkets.

It is on wheels and can easily change location in the shop.

It is ideal for branding for better presentation of the cabinet content.

All the different sizes of this range is optimized for baskets that can hold 5 liter plastic tubs in the top and there is room for storage underneath.

Baskets are optional. Type and number must be ordered under accessories.

Design and Mate	rial	Measures and Co	ntent		Ρ
SneezeGuard	Yes	Temperature Range	°C	-24 to -14	E
Tempered glass	Yes	Climate Class		4	E
slic	2 flat angled	Gross / Net Weight	kg	96 / 89	A
	sliding temp. glass lids	Gross / Net Volume	I	176 / 157	l
Basket No & Type	Additional (see drawings)		· · · · ·		١
Castors	4 wheels, 2 with brake	Cooling and Func	tions		1
Exterior Finish	White	Type of Controller		Mechanical	
Interior Finish	White painted steel	Type of Cooling		Static	
Lock	Yes	Type of Defrost		Manual	I
	105	Refrigerant		R600a	(
		Refrigerant Charge	g	55	E

Thermometer

Power and Consumption					
Energy Class		E			
Energy Consumption	kWh/24h	2.1			
Annual Energy Cons.	kWh/year	767			
Input Power	W	98			
Voltage / Frequency	V/Hz	220-240/50			
Noise Level	dB(A)	45			

D	imensions		
	nternal Dimension WxDxH)	mm	500 x 495 x 710
-	xternal Dimension WxDxH)	mm	720 x 615 x 1295

Yes

Power and Consumption					
Packed Dimension (WxDxH)	mm	800 x 750 x 1200			
40ft Container Load	pcs	92			