

TC57

Ice Maker




Product Features

- Cubed ice approx. 31x35x31mm (18 g)
- Production Capacity: 57 kg/24 h
- Storage Capacity: 28 kg
- Low energy air-cooled system
- Spray system produces individual clear ice cubes
- Self-contained ice machine with storage
- Ag+ easy to clean surfaces in the storage bin
- High quality SS304 stainless steel
- 4 Legs and 4 adjustable feet included
- Scoop for ice cubes included
- Fully automatic



Easy to clean condenser filter



Ice cube dimensions



ECO-FRIENDLY
REFRIGERANT R290

Clear ice maker machine in stainless steel

The TC range of ice makers uses a spray system to produce crystal clear, slow melting ice cubes. This makes the unit ideal for use in cafes, restaurants, pubs, bars, fast-food venues, and other hospitality establishments that require ice for drinks, cocktails, or keeping food such as fresh fish cool.

The exterior of the unit is made from 304 stainless steel; the door at the front of the unit allows quick access to an insulated storage bin, which features Ag+ antibacterial technology to help prevent the formation of bacteria and odors. To ensure that the ice cube maker runs efficiently, the unit has a air filter that is easy to remove and clean.

The TC ice maker uses a low energy air-cooled system, which means it takes in the surrounding air and uses this to cool down the refrigeration system. The capacity of the ice maker is therefore affected by the ambient temperature surrounding it as well as the temperature of the water it takes in.

Design and Material	Measures and Content	Power and Consumption
Feet / Legs	4 adjus Capacity Ice Production	kg/24h Energy Consumption kWh/24h
Exterior Finish	Capacity In Ice Container	kg Annual Energy Cons. kWh/year
	Size of Ice Cubes	mm Power
	Water Consumption	l/24h Max Ambient
	Climate Class	Input Power W
	Gross / Net Weight	kg Voltage / Frequency V/Hz
Cooling and Functions		Dimensions
Type of Controller		External Dimension (WxDxH) mm
Type of Cooling		Packed Dimension (WxDxH) mm
Refrigerant		40ft Container Load pcs
Refrigerant Charge	g	80

14,7

5366

1

40°C at 40% RH

650

220-240/50

500 x 580 x 800

555 x 635 x 965

144